

ECOPLAT / ECOPLAT TP

The New Eco range includes 4 different models all available in transpallet version, the distinguishing mark is the revolutionary control panel that allows a very simple and intuitive use of all the many available wrapping functions.



DISTINGUISHING MARKS

ECOPLAT CONTROL PANEL AND DISPLAY - FUNCTIONS DESCRIPTION



- Spool carriage upward/downward speed adjustable
- Top wraps
- Bottom wraps
- Variable plate rotation speed
- Full wrapping cycle
- Upward cycle-downward cycle
- Manual cycle
- Cycle settings storage (Eco)
- Spool carriage manual lifting
- Spool carriage manual lowering
- Manual homing position
- Spool carriage halt (reinforcement wraps)

TECHNICAL SPECIFICATIONS

ECOPLAT TP	
Turntable for packaging with stretch film transpallet version	
Machine Characteristics	
Plate diameter	1500 mm 1650 mm (Optional)
Max load weight	1200 kg
Max load height	2200 mm
Turntable rotation speed	From 4 to 10 rpm
Variable spool carriage speed	From 1,4 to 4 Mt/ min
Forklifting	Rear
Power supply voltage	230 Volt 1 Ph – 50/60 Hz

ECOPLAT	
Turntable for packaging with stretch film	
Machine Characteristics	
Plate diameter	1500 mm 1650 mm (Optional)
Max load weight	2000 kg
Max load height	2200 mm
Turntable rotation speed	From 4 to 10 rpm
Variable spool carriage speed	From 1,4 to 4 Mt/ min
Forklifting	Front and rear
Power supply voltage	230 Volt 1 Ph – 50/60 Hz