

ROTOWRAP C

ROTOWRAP is the ideal solution for wrapping stretch film around particularly unstable products. Holding the pallet still and stabilizing the product using a rotating arm is a common necessity for many industries. The ROTOWRAP family offers superior-quality products for end-of-line packing technology with machines of excellent design and manufacture that provide fast and efficient pallet wrapping.



TECHNICAL SPECIFICATIONS

ROTOWRAP C Rotating Arm Stretch Wrapping Machine	
Carriages	FR: Film stretch with electro-mechanical brake PDS: Double pre-stretch system
Machine Characteristics	
Arm rotation speed	4÷12 rpm
Upward/downward carriage speed	1,6 ÷ 4,4 m/min
Power supply voltage	230 Volt 1 Ph - 50/60 Hz
Installed power (Rotowrap C - PDS)	1,9 kW
Machine's height	3200 mm
Machine's weight (Rotowrap C - FR)	730 Kg
Machine's weight (Rotowrap C - PDS)	750 Kg

Characteristics of the product to be wrapped	
Maximum dimensions (LxW):	1000 x 1200 mm
Maximum useful height:	2200 mm

Film spool characteristics	
Max. external diameter (D):	300 mm
Film spool height (h):	500 mm
Film thickness:	17-35 µm
Internal diameter (d):	76 mm
Max. weight:	20 kg