

WRAP AROUND SHRINK WRAPPER – GOLD STAR

ST@R is the most advanced series of machines currently found on the heat shrink film packaging machine market. “Top Level” electronic ST@R machine management allows high production performance.



ST@R series machines are designed for easy operator use. In fact, the touch screen panel can be used to control all machine parameters and production statistics, manage and modify sizes and integrally control tunnel temperatures.

ST@R machines are prepared for connection to a centralised production data management network. The maximum monitoring level can be reached via modem (option) to permit problem diagnosis, program settings and up-upgrades.

ST@R machines are available in the unique frame version and in the modular frame version (option), for single line and for double line (BIG).

SUITABLE FOR THE FOLLOWING PRODUCTS

Bottles	(P.E.T. / GLASS / HDPE)
Cans	(ALUMINUM / STEEL)
Pots	(P.E.T. / GLASS / HDPE)
Multipacks	(CLUSTER, FILM, ASTUCCI)
Bricks	

SINGLE LINE

- GOLD ST@R F CONT. (up to 60 packs/min) Film Only
- GOLD ST@R P CONT. (up to 60 packs/min) Pad+Film
- GOLD ST@R T CONT. (up to 60 packs/min) Tray+Film

DOUBLE LINE

- GOLD ST@R F BIG CONT. (up to 60+60 packs/min) Film Only
- GOLD ST@R P BIG CONT. (up to 60+60 packs/min) Pad+Film
- GOLD ST@R T BIG CONT. (up to 60+60 packs/min) Tray+Film

TECHNICAL SPECIFICATIONS - BLUE ST@RÈ

GOLD ST@R							
		SINGLE TRACK			DOUBLE TRACK		
		60 PPM			60+60 PPM		
	F	P	P	T	F	P	T
Overall length	mm	11770	11770	12810	11770	11770	12810
	inches	463.4	463.4	554.3	463.4	463.4	554.3
Machine width (+main electrical cabinet)	mm		1200 (+ 585)			1600 (+ 585)	
	inches		47.2 (+ 23)			63 (+ 23)	
Working height	mm		1070 - 1365			1070 - 1365	
	inches		42.1 - 53.7			42.1 - 53.7	
Total power	kW	105	106	110		116.4	
Air consumption	NI/min		100			100	
Air pressure	BAR		6			6	

ELECTRONICAL CONTINUOUS SEPARATION SYSTEM (PATENTED)



Control by photocells for correct product position and for minimum product accumulation in each lane, control for the fallen

product. Continuous separation system driven by servomotors to separate products through a double couple of teeth with lower introduction between the products.

PRODUCTS TRANSFER GROUP WITH BARS



After the collation of the products into the required configuration, the block of the products is transferred to couple with the tray

or the pad. The group is complete with plastic lateral guide rails in order to obtain a perfect products compacting. The group is equipped with torque limiter that safeguards the bars group from eventual accidental stops.

BLANK PICK-UP (only "T" version and "P" version)



The blank is picked up by a rotating arm with suckers from the magazine. The suckers use the vacuum pump. The blanks stand on a conveyor driven with a step-by-step motion. The picked up blank is put on a chain conveyor and then coupled with the product.

FILM UNWINDING SYSTEM



The film reel are placed on two pneumatic expanding shafts. The system is complete with manual sealer for film splicing. Film is kept constantly

in tension thanks to a pneumatic compensation group. The film reel are disk braking, with direct action on the expanding shafts in order to allow the correct film tension at the beginning or at the end of the roll. The group is equipped with antistatic bars to eliminate electrostatic charges.

PRODUCTS WRAPPING (PATENTED)



Film transport bars are fixed on a rotary support only on one side to allow a full accessibility to the wrapping group. Simple

manual adjustments with digital counters allow to wrap a wide range of packs without any parts replacement. Also this group is equipped with torque limiter to safeguard from eventual accidental stops.

TRAY FORMATION (only "T" version)



The tray is erected in continuous by wrap-around system. The first flap is folded with the arrival of the front teeth of the chain; during the way, the blank is coupled with the product. The back flap is folded by the rear teeth of the chain. Then there is the folding of the front lateral flaps with fixed contrasts while the back ones are folded by folders driven by a mechanical contrast. At this point the glue is applied on the side flaps which, while advancing in continuous motion, are folded by a pneumatic cam. Finally, the lateral flaps are lift to couple with the already glued flaps to complete the tray.

FILM CONTROL AND CUTTING SYSTEM



Cutting group with rotating shaft driven by a friction brake group. Film unwinding and thrusting driven by servomotors. The group is equipped

with pneumatic input for rollers opening, in order to allow an easier film insertion. The upper belt has a tilt opening which allows the full inspection of the cutting group, the blade replacement or the complete cleaning of the group.

SHRINK TUNNEL



Products go on a mesh belt driven by rubber rollers. The belt tensioning is kept constant by a damper weight placed on the last part of the tunnel.

The tunnel is equipped with external adjustment to optimise the air flows according to the pack configuration. Manual device to empty the tunnel when no voltage is supplied. Cooling fan placed at the end of the tunnel to force the beginning of the shrink. Lateral panels can be dismantled for resistances replacement.