

SEMI-AUTOMATIC STRAPPING MACHINE

FEATURES

- Standard accessory, its advantage is stable quality, durable material, and easy maintenance.
- Special design-Control PP straps cooling time. It can make the PP strap to fasten well in any time.
- "Electricity-saving" device, the motor automatically stops running after 60 seconds pause to reduce the regular mechanical wear and to prolong the machine's life.
- The advanced P.C.B microchip circuit board control system, less malfunction and easy maintenance.
- Durable electro-magnetic clutch transmission means lesser mechanical wear and noise pollution.
- New heater plate design improves warm-up-time, welding speed and increase work efficiency.
- Installing an auxiliary feed switch and cut switch at the control panel makes you operate more conveniently.



Model	PW-316H	PW-316L	PW-316SL
Power Supply		1 AC110,220V(50,60Hz), 1/4HP)	
Strap Width		9,12,15.5 (mm), (adjustable)	
Tension Strength		15-50 kgs	
Strapping Speed		2.0 sec/strap	
Min. Package Size		60 mm	
Max. Package Size		Any Size	
Dimension (LxWxH) (mm)	910x580x750	1490x580x480	1510x58xx33x
N.W	100 kgs	90 kgs	80 Kgs
G.W	120 kgs	110 kgs	90 Kgs
Packing Size (LxWxH)(mm)	956x626x842	956x626x592	Machine: 956x626x746 Dispenser: 956x626x443